

5-100

A

04/28/00

Jc520 U.S. PTO

**UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
49794(904)Total Pages in this Submission
57**TO THE ASSISTANT COMMISSIONER FOR PATENTS**Box Patent Application
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

OPTICAL DISK, OPTICAL REPRODUCTION DEVICE, AND OPTICAL RECORDING DEVICE

and invented by:

JUN AKIYAMA, SHIGEMI MAEDAJc578 U.S. PTO
09/560522
04/28/00If a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Enclosed are:

Application Elements

- ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 47 pages and including the following:
- a. ☒ Descriptive Title of the Invention
 - b. ☐ Cross References to Related Applications (if applicable)
 - c. ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
 - d. ☐ Reference to Microfiche Appendix (if applicable)
 - e. ☒ Background of the Invention
 - f. ☒ Brief Summary of the Invention
 - g. ☒ Brief Description of the Drawings (if drawings filed)
 - h. ☒ Detailed Description
 - i. ☒ Claim(s) as Classified Below
 - j. ☒ Abstract of the Disclosure

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
49794(904)

Total Pages in this Submission
57

Application Elements (Continued)

3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*
- a. ☒ Formal Number of Sheets 10
- b. ☐ Informal Number of Sheets _____
4. ☒ Oath or Declaration
- a. ☒ Newly executed *(original or copy)* ☐ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☒ With Power of Attorney ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application,
see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference *(usable if Box 4b is checked)*
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under
Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby
incorporated by reference therein.
6. ☐ Computer Program in Microfiche *(Appendix)*
- ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*
- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

Accompanying Application Parts

8. ☒ Assignment Papers *(cover sheet & document(s))*
9. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*
10. ☐ English Translation Document *(if applicable)*
11. ☐ Information Disclosure Statement/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☒ Certificate of Mailing
- ☐ First Class ☒ Express Mail *(Specify Label No.):* EL05457017US

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
49794(904)

Total Pages in this Submission
57

Accompanying Application Parts (Continued)

15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Additional Enclosures (please identify below):


--

Fee Calculation and Transmittal

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	17	- 20 =	0	x \$18.00	\$0.00
Indep. Claims	6	- 3 =	3	x \$78.00	\$234.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$690.00
OTHER FEE (specify purpose) Assignment Recordal					\$40.00
TOTAL FILING FEE					\$964.00

- ☒ A check in the amount of \$964.00 to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. 04-1105 as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of _____ as filing fee.
- ☒ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).


Signature

Dated: April 28, 2000

David A. Tucker
Reg. No. 27,840
Dike, Bronstein, Roberts & Cushman, LLP
130 Water Street
Boston, MA 02109
617-523-3400

CC:

OPTICAL DISK,
OPTICAL REPRODUCTION DEVICE, AND
OPTICAL RECORDING DEVICE

FIELD OF THE INVENTION

The present invention relates to optical disks and optical disk devices, and in particular, to optical disks, optical reproduction devices, and optical recording devices that are capable of performing reliable recording and reproduction.

BACKGROUND OF THE INVENTION

We have in recent years witnessed digital information being offered in dramatically increasing quantities, as various contents including video and audio have become available in digital format. In response to

00560527 042000
000240 22005600

this trend, development is under way to design optical disk devices suitable to increasing capacity and density. Meanwhile, considering that the quality of reproduction signals deteriorates with increase in density, various solutions are suggested to improve the quality of reproduction signals.

Reproduction signals carry, in addition to image and other main information, servo information and other various kinds of control and management information. Among those kinds of information, clock information is one of the most important, because it serves as a reference for operations of all the circuits that record or reproduce information. Japanese Laid-Open Patent Application No. 11-16216/1999 (Tokukaihei 11-16216; published on January 22, 1999) discloses an optical disk and an optical disk device that are capable of performing error-free readout with improved clock information quality.

The above conventional optical disk and optical disk device will be further explained in the following.

First, the format of the optical disk will be explained. Figure 6(a) shows an arrangement of a sector. Each sector is divided into 46 segments. Each segment serves either as an address segment or as a data segment. Here, AS0 located at the head of the sector serves as an

address segment, while DS0 to DS44 as data segments.

Figure 6(b) shows an arrangement of an address segment. The address segment includes a clock mark field (CM field), an address field, a preamble field, and other fields. In each field, a predetermined signal is recorded in advance in the form of a variation in the shape of a pit or groove.

The clock mark field records in advance a clock mark from which a clock signal is generated as mentioned in the foregoing. The address field records the address of the sector. The other fields are provided as necessary so as to control address readout or ensure a readout margin.

Figure 6(c) shows an arrangement of a data segment. The data segment includes a clock mark field (CM field) at its head as does the address segment. The other field serves as a data field, where main information is recorded and reproduced by a magneto-optical recording technique. Each segment is 63.5 byte long, for example. Clock marks are then found at identical intervals equaling 63.5 bytes.

Next, the clock mark will be explained. Figure 7 shows a clock mark on the disk. The clock mark is formed in the form of a convexity in the groove and of a concavity in the land as shown in Figure 7, causing a fluctuation in the quantity of light with a move of a

laser spot along the tangent of the track. The clock mark is detected, using a photodetector divided perpendicular to the tangent of the track into two parts, as a differential signal, i.e., a tangential push-pull signal (TPP signal), supplied by those two parts of the photodetector. Figure 7 shows how the TPP signal fluctuates. Cyclic clock signals are detected by binarizing the TPP signal using, for example, a zero-cross comparator.

The aforementioned detection of a clock signal from the clock mark allows the shape and other parameters of the clock mark to be specificized independently from the main information recorded by a magneto-optical recording technique. In addition, the use of TPP signals better prevents the conditions under which tracking is controlled from negatively affecting the detection of a clock signal than the use of push-bull signals. These factors contribute improvement of the quality of signals. Therefore, a clock can be reproduced with a relatively short mark length, and opens up a possibility to further increase the recording density, compared to the clock information recorded in wobbles whereby the side walls of a track groove are formed with wobbles.

Now, the conventional optical disk device will be explained. Figure 8 shows a diagram representing an

00550522-042800

arrangement of major components of a recording and reproduction signal processing section for use with an optical disk. The optical disk 1 is rotated by a spindle motor 2. The optical disk 1 may be of any type; here, the explanation will be made based on the assumption that the optical disk 1 is a magneto-optical disk.

The optical disk 1 is irradiated on its bottom surface with a light beam projected through an objective lens 3 disposed on a pickup 4. The intensity of the light beam is suitably controlled by the LD drive circuit 6, and hence differs between recording and reproduction operations. The light reflected at the optical disk 1 is detected by a photodetector provided inside the pickup 4. The reflection is separated into a TPP signal, an RF signal, and a servo signal (not shown).

Bit clocks are generated from the TPP signal by a clock generation circuit 13. The foregoing description tells that only one clock signal is detected from each segment, because each segment contains only one clock mark; however, bit clocks are generated in plurality with a suitably increased ratio by means of a built-in PLL circuit in the clock generation circuit 13. Here, since each segment is specified to include 63.5 bytes of data, 508 (63.5 bytes \times 8 bits) bit clocks are generated per segment.

00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000

The generated bit clocks are supplied to data processing and other circuits, including a demodulation circuit 14, a modulation circuit 8, an A/D converter 11, a reproduction data processing circuit 15, and a recording data processing circuit 10 as necessary. The RF signal is sampled by the A/D converter 11, and then demodulated by the demodulator circuit 14.

The signal demodulated by the demodulator circuit 14 is transmitted to the reproduction data processing circuit 15, where the demodulated signal is processed so as to recover data therefrom. Errors found in the data recovered in the reproduction data processing circuit 15 are corrected in an error correction circuit 17.

For recording, the data with an additional error correction code provided in the error correction circuit 17 is sent to the recording data processing circuit 10, where the received data is divided into sets of data to be recorded in respective segments, so as to generate sector data. Each set of data is then modulated by the modulation circuit 8 into predetermined modulated signals. The modulated signals are translated into a magnetic field by a magnetic head drive circuit 7 and a magnetic head 5. The magnetic field in turn records information on the optical disk 1 in collaboration with a light beam emitted by the pickup 4.

0050522 01200

First, the explanation will focus on the recording and reproduction operation performed by the conventional optical disk device under normal conditions, that is, when the clock mark is not defective.

For reproduction, the address segment located at the head of the sector is reproduced to confirm that the reproduced address matches the target address. If so confirmed, the data segment is reproduced. Only the data is recovered and transmitted to the error correction circuit 17, where error correction is performed in predetermined procedures. The conventional optical disk device thus performs recording and reproduction operation.

The recording and reproduction operation mentioned in the foregoing can be performed in a stable manner regardless of the quality of signals reproduced from a

data field, because of the use of bit clocks generated from high-quality clock signals.

Incidentally, the detection of clock signals by means of clock marks boasts excellent performance. The method, however, is susceptible to disk flaws, because the use of clock marks enables the detection of clock signals with shorter mark lengths, but inevitably increases, with decreasing mark lengths, the likelihood of the presence of even a small flaw negatively affecting the clock mark. A normal clock signal cannot be detected from a clock mark, if the clock mark is defective due to a flaw.

Now, the explanation will focus on the recording operation performed by the conventional optical disk device with the optical disk 1 when a clock mark is defective due to a flaw.

Figure 9 shows, in its top half, the position of data recorded on the optical disk 1 under normal conditions. The sets of data recorded in the respective data segments DS0 to DS44 are identical in size to each other, while the bit clocks in those data segments are also identical in number at 508 to each other; therefore, the data segments have equal lengths.

Figure 9 shows, in its bottom half, the position of data recorded on the optical disk 1 when a clock mark is

00550522.042800

Since the frequency of the bit clocks decreases, the data is recorded in the data segment DS3 with extended mark lengths in comparison to standard mark lengths. The data, which would normally be recorded in its entirety in the data segment DS3, does not fit into the data segment DS3 with its tail spilling over into the head, i.e., the clock mark field, of the data segment DS4. Let us assume that the number of bits spilled over equals N .

The aforementioned explanation may be rephrased with a term, "the number of bit clocks in a data segment." The standard number of bit clocks in a data segment equals 508 as mentioned in the foregoing. However, the defect in the clock mark located at the head of the data segment

DS3 lowers the frequency, that is, extends the cycle, of the bit clocks in the data segment DS3 and thereby reduces the number of the bit clocks to 507 or even further. Here, it is assumed that the number of bit clocks in the data segment DS3 equals 508-N.

Meanwhile, the clock mark located at the head of the data segment DS4 restores the frequency of the bit clocks to a standard frequency, enabling the data after that to be recorded with normal mark lengths. However, since the data segment DS3 is extended by N bits in recording, the sets of data recorded in the data segments subsequent to the data segment DS3 are displaced by N bits. Hence, the last N bits of each set of data that should have been recorded in the data field of one of the data segments DS3 to DS44 are displaced and recorded in the clock mark field of the subsequent data segment. The displacement is corrected when the address segment located at the head of the subsequent sector is reproduced. Beginning from the first data segment of the subsequent sector, the data is recorded without being displaced.

Now, the explanation will focus on the reproduction operation performed by the conventional optical disk device when the data includes some bits that are displaced in a recording operation. The reproduction data processing circuit 15 includes a built-in buffer memory

00000000000000000000000000000000

for temporarily recording data. Figure 10 shows, in its top half, the position of data recorded in the buffer memory under normal conditions, and, in its bottom half, the position of data recorded in the buffer memory when the clock mark is defective.

The arrangement of reproduction data in the buffer memory is determined by bit clocks from the clock generation circuit 13. The defect is present only in the clock mark field of the data segment DS3. Therefore, up to the data segment DS2, the data is not at all affected by the defect: the data can be reproduced correctly and arranged in standard position. At the head of the data segment DS3 where the clock mark is defective due to a flaw, clocks are not generated normally in a data reproduction operation. Hence, the frequency of the clocks is increased or decreased over the standard frequency.

Supposing that the frequency of the bit clocks deviates identically in recording and reproduction operations, the data in the data segment DS3 can be reproduced normally except the last N bits recorded in the clock mark field of the data segment DS4.

However, typically, conditions differ between recording and reproduction operations, and hence the frequency does not deviate identically. When this is the

00000000000000000000000000000000

case, the number of bit clocks in the data segment DS3 in a reproduction operation differs from that in a recording operation, obstructing normal reproduction. Let us assume here that the difference of bit clocks in number between recording and reproduction operations corresponds to M bits.

At the head of the data segment DS4 where another clock mark is located, the frequency of the bit clocks is restored to a standard, enabling error-free reproduction of data in the data segment DS4 and its subsequent data segments. Note that the aforementioned displaced N bits cannot be reproduced, because they have failed to be recorded in a standard segment range, spilling over into the head of the subsequent data segment. In other words, in each of the data segments DS4 to DS44, the last N bits of data are lost, whereas the rest of the data is reproduced normally.

The data is reproduced correctly on a bit-by-bit basis. However, if the number of clocks corresponding to the data segment DS3 differs between recording and reproduction operations, the data in the data segment DS4 and its subsequent data segments is not divided correctly into 1-byte pieces of data. Typically, data reproduction, error correction, and other operations are performed on a byte-by-byte basis; if the data is not correctly

00550522:042800

divided into 1-byte sets of data, the data cannot be reproduced correctly.

As mentioned in the foregoing, in the data segment DS3, there exists a difference in the number of bit clocks between recording and reproduction operations, corresponding to M bits. Therefore, the data in the data segment DS4 and its subsequent data segments are displaced by M bits, causing none of that data to be reproduced correctly. Figure 10 shows the data being displaced by M bits off a standard data position.

In short, if the conventional optical disk and optical disk device fails to correctly detect the clock signal, the data is displaced and cannot be recorded and reproduced.

SUMMARY OF THE INVENTION

The present invention, in view of the above problems, has an object to offer an optical disk, an optical reproduction device, and an optical recording device that are capable of performing highly reliable recording and reproduction even if a clock mark is defective due to a flaw.

In order to achieve the object, an optical disk in accordance with the present invention is characterized in that it includes data segments, for recording data,

00550522 042200

provided in each sector in a recording track, wherein

at least some of the data segments each include:

a clock mark field for recording a clock mark from which a clock signal is obtained; and

a synchronization field for recording a synchronization pattern with which displacement of data is corrected.

With the arrangement above, data segments for recording data are provided in each sector in a recording track.

Conventionally, a clock mark is used in detection of a clock signal so as to reproduce the clock signal, which constitutes important information, without error. However, the clock mark has a drawback where it easily becomes defective even due to a small flaw in the optical disk. A normal clock signal cannot be obtained from a clock mark, if the clock mark is defective, displacing the data off standard position. Conventionally, if a defective clock mark exists in the optical disk, all data after the displaced data includes an error in the sequential reproduction of the data, failing to reproduce large data correctly.

Accordingly, by adopting the arrangement in accordance with the present invention, at least some of the data segments have a clock mark field and a

00560522-042800

synchronization field, a clock signal is obtained from the clock mark recorded in the clock mark field, and the displacement of data can be corrected according to the synchronization pattern recorded in the synchronization field.

In other words, the displacement of the data caused by a defective clock mark can be corrected according to the synchronization pattern recorded in the synchronization field in the data segment for subsequent data so as to restore the data in subsequent data segments to standard position. Therefore, the error caused by the displacement is confined to a minimum amount of data, allowing large data to be reproduced correctly.

Further, in order to achieve the object, an optical reproduction device in accordance with the present invention is an optical reproduction device for reproducing data recorded in data segments provided in each sector in a recording track of an optical disk,

the optical reproduction device is characterized in that it includes:

a clock generation circuit for generating a clock signal from a clock mark recorded in a clock mark field provided in the data segments; and

a data rearrangement circuit for detecting a

00560521 042800

A defect in the clock mark obstructs the generation of a correct clock signal by the clock generation circuit and causes displacement of the data when recorded; however, with the arrangement above, the displacement can be corrected according to the synchronization pattern detected by the data rearrangement circuit. Therefore, the data in the data segments subsequent to the data segment for the displaced data can be reproduced correctly. This realizes highly reliable recording and reproduction with few data errors.

Further, in order to achieve the object, an optical recording device in accordance with the present invention is an optical recording device for recording data in data segments provided in each sector in a recording track of an optical disk,

the optical recording device is characterized in that it includes:

a clock generation circuit for generating a clock signal for use in recording of the data; and

a synchronization pattern addition circuit for
adding a synchronization pattern for correcting

displacement of the data to data recorded in at least some of the data segments.

With the arrangement above, a synchronization pattern is added to data recorded in at least some of the data segments; therefore, even if a defective clock mark causes the data to be displaced when recorded, the data in the data segments subsequent to the data segment for the data displaced can be recorded correctly by correcting the displacement according to a synchronization pattern in a data segment subsequent to the data segment for the displaced data. Therefore, the error caused by the displacement is confined to a minimum amount of data, allowing large data to be reproduced correctly. This realizes highly reliable recording and reproduction with few data errors.

For a fuller understanding of the nature and advantages of the invention, reference should be made to the ensuing detailed description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1(a) to Figure 1(c) are explanatory drawings showing a format of an optical disk of an embodiment in accordance with the present invention.

Figure 2 is an explanatory drawing showing kinds of

00550222.042300

information recorded in a data segment of an optical disk of an embodiment in accordance with the present invention.

Figure 3 is a block diagram showing an optical disk drive (optical recording device, optical reproduction device) of an embodiment in accordance with the present invention.

Figure 4 is an explanatory drawing showing the position of data on a disk of an embodiment in accordance with the present invention.

Figure 5 is an explanatory drawing showing the position of data in a buffer memory provided in a data rearrangement circuit of an optical disk drive of an embodiment in accordance with the present invention.

Figure 6(a) to Figure 6(c) are explanatory drawings showing a format of a conventional optical disk.

Figure 7 is an explanatory drawing showing clock marks and a fluctuation in a TPP signal caused by a clock mark on a conventional optical disk.

Figure 8 is a block diagram showing a conventional optical disk drive (optical recording device, optical reproduction device).

Figure 9 is an explanatory drawing showing the position of data recorded on a conventional optical disk.

Figure 10 is an explanatory drawing showing the

00550522-042800

position of data recorded on a buffer memory used with a conventional optical disk device.

DESCRIPTION OF THE EMBODIMENTS

Referring to the drawings, the following description will discuss an embodiment in accordance with the present invention.

Figure 1(a) to Figure 1(c) are explanatory drawings showing a format of an optical disk in accordance with the present invention. Figure 1(a) shows an arrangement of a sector. Each sector is constituted by two address segments AS0 and AS1 and 45 data segments DS0 to DS44. The number of the address segments and data segments shown here may be changed according to use.

Figure 1(b) shows an arrangement of an address segment. The address segments AS0 and AS1 each include a clock mark field (CM field), an address field, a preamble field, and other fields. In each field, a predetermined signal is recorded in advance in the form of a variation in the shape of a pit or a groove.

The clock mark field records in advance a clock mark from which a clock signal is generated as mentioned in the foregoing. The address field records the address of the sector. The other fields are provided as necessary so as to control address readout or ensure a readout margin.

Figure 1(c) shows an arrangement of a data segment. The data segment is constituted by a clock mark field (CM field), a pre-write field, a post-write field, and a data field. The clock mark field in the data segment records a clock mark as does the clock mark field in the address segment. The clock mark field (clock field) is designed so as to have a different light reflectance from that of the data field. The pre-write and post-write fields are for offsetting the displacement of data that occur in a recording operation. The preceding and subsequent data segments are not negatively affected by the displacement of data that occur in a recording operation, provided that the displacement is confined within this range.

Each segment is 63.5 byte long, for example. Clock marks are then found at identical intervals equaling 63.5 bytes.

Figure 2 is an explanatory drawing showing sets of data recorded in respective data segments. The data field of the first data segment DS0 after the two address segments records a pattern called header pattern. The header pattern is used to match the clock and the data in phase, and is selected so as to suitably achieve that purpose. Suitable, specific examples include a cyclic pattern where the edge of data does not change its position.

20250522 042800

The subsequent data segments DS1 to DS44 record data, and include synchronization fields each provided for every predetermined number of data segments in the data field. In Figure 2, "S" denotes a synchronization field. In the present embodiment, a synchronization field is provided for every two data segments. A rarely occurring pattern that produces high quality signals and has relatively long mark lengths is selected as the synchronization pattern recorded in the synchronization field.

Now, the following description will discuss an optical disk device of an embodiment in accordance with the present invention. Figure 3 is a block diagram representing an arrangement of major components of a recording and reproduction signal processing section for use with an optical disk. The optical disk 1 is rotated by a spindle motor 2. The optical disk 1 may be of any type; here, the description will be made based on the assumption that the optical disk 1 is a magneto-optical disk.

The optical disk 1 is irradiated on its bottom surface with a light beam projected through an objective lens 3 disposed on a pickup 4. The intensity of the light beam is suitably controlled by the LD drive circuit 6, and hence differs between recording and reproduction

00550522:042800

Bit clocks are generated from the TPP signal by a clock generation circuit 13 (clock generate means). The foregoing description tells that only one clock signal is detected from each segment, because each segment contains only one clock mark; however, bit clocks are generated in plurality with a suitably increased ratio by means of a built-in PLL circuit in the clock generation circuit 13. Here, supposing that each segment is specified to include 63.5 bytes of data for example, $508 \text{ (} 63.5 \text{ bytes} \times 8 \text{ bits)}$ bit clocks are generated per segment.

The modulation and demodulation may possibly be performed by various techniques: NRZI is an example suitable for use in high density recording and reproduction, since the technique allows for a great

The signal demodulated by the demodulator circuit 14 is transmitted to the reproduction data processing circuit 15, where the demodulated signal is processed so as to recover data therefrom. The phase adjusting circuit 12 adjusts a phase according to signals from the clock generation circuit 13 and the A/D converter 11. The data rearrangement circuit (synchronization pattern detection means, reproduction means) 16 rearranges the data according to the synchronization signal contained in the data. Errors found in the rearranged data are corrected in an error correction circuit 17.

For recording, the data with an additional error correction code provided in the error correction circuit 17 is sent to the recording data processing circuit 10, where the received data is divided into sets of data to be recorded in respective segments. A

header/synchronization signal addition circuit (synchronization pattern addition circuit) 9 adds a re-synchronization pattern and a header pattern to the output from the recording data processing circuit 10 so as to generate sector data. Each set of data is then modulated by the modulation circuit 8 into NRZI codes. The signals modulated into NRZI codes are translated into a magnetic field by a magnetic head drive circuit 7 and a magnetic head 5. The magnetic field in turn records information on the optical disk 1 in collaboration with a light beam emitted by the pickup 4.

First, the explanation will focus on the recording and reproduction operation under normal conditions, that is, when the clock mark is not defective.

For recording, the address recorded in advance in the address segment located at the head of the sector is reproduced so as to confirm that the reproduced address matches the target address. If so confirmed, a header pattern for introducing a phase is recorded in the first data segment. The data with an additional error correction code provided in the error correction circuit 17 is recorded in the subsequent data segments. Further, recording means records a synchronization pattern as well as data for every predetermined number of data segments. The recording means is constituted by the

00560522.042000

For reproduction, the address segment located at the head of the sector is reproduced to confirm that the reproduced address matches the target address. If so confirmed, the bit clocks generated by the clock marks are adjusted in phase with the header pattern by using the header pattern recorded in the first data segment.

Specifically, the phase adjusting circuit 12 is adjusted so that the data signal supplied to the reproduce data process circuit 15 matches with the bit clock signal in phase according to the comparison of the two signals. The phase adjustment serves as a correction of the deviation in phase caused by the difference in the recording and reproduction method between the clock mark recorded in the form of a fine variation in the shape of the optical disk 1 and the data recorded in the form of magneto-optic signals. The effects of the deviation in phase can be eliminated by the provision of the header pattern in the data segment DS0 located at the head of the sector and the adjustment of the phase using the header pattern.

Subsequently, an immediately following data segment is reproduced. Since a synchronization pattern is provided for every predetermined number of data segments, the data rearrangement circuit 16 detects a synchronization pattern, and byte synchronization is performed where data is rearranged with positions dividing a set of data into 1-byte subsets of data being used as standard positions.

The synchronization pattern is detected only in proximity to a synchronization pattern in a data segment. Specifically, the data rearrangement circuit 16 includes an internal window circuit (window means) by means of which the synchronization pattern is detected only in a certain period of time following a predetermined period of time after a reference position signal such as the clock mark in a segment. With such a circuit arrangement, the synchronization pattern is not detected in a data field; therefore, a data pattern, found in data, identical or similar to the synchronization pattern can be prevented from wrongly detected as being a synchronization pattern.

Only the data which has been rid of the synchronization pattern and other command signals and has undergone byte synchronization in the data rearrangement circuit 16 is transmitted to the error correction circuit

17, where error correction is performed in predetermined procedures. The optical disk device thus performs recording and reproduction operation.

Now, the explanation will focus on the recording operation performed with the optical disk 1 when a clock mark is defective due to a flaw.

Figure 4 shows, in its top half, the position of data recorded on the optical disk 1 under normal conditions. The sets of data recorded in the respective data segments DS0 to DS44 are identical in size to each other, while the bit clocks in those data segments are also identical in number at 508 to each other; therefore, the data segments have equal lengths.

Figure 4 shows, in its bottom half, the position of data recorded on the optical disk 1 when a clock mark is defective. Here, an example is taken where the clock mark located at the head of the data segment DS3 is defective. The defect of the clock mark disrupts normal generation of bit clocks in the clock generation circuit 13, resulting in the generation of bit clocks with a higher or lower frequency than that of the standard bit clocks. Whether the frequency of the bit clocks increases or decrease over that of the standard bit clocks is determined by variations in the frequency and other conditions of the bit clocks of the data segment DS3 and

00550522.042800

its preceding data segments. Here, the explanation will focus on bit clocks with a decreased frequency.

As the frequency of the bit clocks decreases, the data is recorded in the data segment DS3 with extended mark lengths in comparison to standard mark lengths. The data, which would normally be recorded in its entirety in the data segment DS3, does not fit into the data segment DS3 with its tail spilling over into the head, i.e., the clock mark field, of the data segment DS4. Let us assume that the number of bits spilled over equals N.

The aforementioned explanation may be rephrased with a term, "the number of bit clocks in a data segment." The standard number of bit clocks in a data segment equals 508 as mentioned in the foregoing. However, the defect in the clock mark located at the head of the data segment DS3 lowers the frequency, that is, extends the cycle, of the bit clocks in the data segment DS3 and thereby reduces the number of the bit clocks to 507 or even further. Here, it is assumed that the number of bit clocks in the data segment DS3 equals 508-N.

Meanwhile, the clock mark located at the head of the data segment DS4 restores the frequency of the bit clocks to a standard frequency, enabling the data after that to be recorded with normal mark lengths. However, since the data segment DS3 is extended by N bits in recording, the

003340 22205500

Now, the explanation will focus on the reproduction operation when the data includes some bits that are displaced in a recording operation. The data rearrangement circuit 16 includes a built-in buffer memory for temporarily recording data. Figure 5 shows, in its top half, the position of data recorded in the buffer memory under normal conditions, and, in its bottom half, the position of data recorded in the buffer memory when the clock mark is defective.

The defect is present only in the clock mark field of the data segment DS3. Therefore, up to the data segment DS2, the data is not at all affected by the defect: the data can be reproduced correctly and arranged in standard position. At the head of the data segment DS3 where the clock mark is defective due to a flaw, clocks

are not generated normally in a data reproduction operation. Hence, the frequency of the clocks is increased or decreased over the standard frequency. Supposing that the frequency of the bit clocks deviates identically in recording and reproduction operations, the data in the data segment DS3 can be reproduced normally except the last N bits recorded in the clock mark field of the data segment DS4. However, typically, conditions differ between recording and reproduction operations, and hence the frequency does not deviate identically. When this is the case, the number of bit clocks in the data segment DS3 in a reproduction operation differs from that in a recording operation, obstructing normal reproduction. Let us assume here that the difference of bit clocks in number between recording and reproduction operations corresponds to M bits.

At the head of the data segment DS4 where another clock mark is located, the frequency of the bit clocks is restored to a standard, enabling error-free reproduction of data in the data segment DS4 and its subsequent data segments. Note that the aforementioned displaced N bits cannot be reproduced, because they have failed to be recorded in a standard segment range, spilled over into the head of the subsequent data segment. In other words, in each of the data segments DS4 to DS44, the last N bits

of data are lost, whereas the rest of the data is reproduced normally.

The data is reproduced correctly on a bit-by-bit basis. However, if the number of clocks corresponding to the data segment DS3 differs between recording and reproduction operations, the data in the data segment DS4 and its subsequent data segments is not divided correctly into 1-byte pieces of data.

Accordingly, in the present embodiment, a synchronization pattern is recorded in every two data segments as mentioned in the foregoing. The synchronization pattern is detected, and the data is rearranged by the data rearrangement circuit 16 so as to be correctly divided into 1-byte pieces of data. The first synchronization pattern after that in the data segment DS3 is recorded in the data segment DS5; therefore, as the synchronization pattern recorded in the data segment DS5 is detected, the data is brought forward by M bits.

Figure 5 shows, in its bottom half, the position of data recorded in the buffer memory after the data is rearranged. As can be shown here, the data in the data segment DS5 and its subsequent data segments is rearranged into the same position that is identical to the standard data position shown in the top half of

00000000000000000000000000000000

Figure 5. The data thereby can be divided into 1-byte pieces, i.e., re-synchronized, in a reproduction operation.

In the present embodiment, the explanation has so far focused on bit clocks with a decreased frequency due to a missing clock mark. However, it would be clear that, when the present embodiment is applied to bit clocks with an increased frequency, the same explanation holds true except that the deviation of data by N or M bits occurs in the opposite direction, and the present embodiment therefore has the same advantages.

Further, in the present embodiment, a synchronization pattern is so far recorded in every two data segments. If a synchronization pattern is recorded in every data segment for example, the data is rearranged in the data segment DS4 and thereby divided correctly into 1-byte pieces; therefore, the data is re-synchronized earlier than in the present embodiment. A tradeoff is that the fields used as synchronization fields double in number, which leaves less data fields available for use by the user. As can be observed here, the frequency in provision of the synchronization patterns and the amount of data available for use by the user cannot be increased simultaneously, and hence are determined according to use. When reliability should be

given a higher priority, the frequency in provision of the synchronization patterns is increased; by contrast, when the amount of data should be given a higher priority, the frequency in provision of the synchronization pattern is decreased.

Besides, the intervals between the synchronization patterns may be varied; however, identical intervals are preferred as in the present embodiment. If the synchronization patterns are not provided at regular intervals with one of them being longer than the others, and the clock mark is missing in the longer interval, it takes longer before the data is re-synchronized. By contrast, if the synchronization patterns are provided at regular intervals, and a clock mark is missing on any given part of the disk, the data is re-synchronized after a certain period of time.

Moreover, the synchronization pattern preferably has a fixed position in the segment as it is in the present embodiment. The synchronization pattern is selected so that an identical pattern rarely occurs; however, a possibility is that a pattern identical to the synchronization pattern appears mixed in a reproduction signal due to a defect. Also, in some modulation schemes, such a rarely occurring pattern cannot be selected. If the synchronization pattern has a fixed position in the

segment, an arrangement is readily made so that the detection of synchronization patterns is performed only in proximity to where the synchronization pattern is expected to be found, not in those places where no synchronization pattern is expected to be found, which eventually prevents the synchronization pattern from wrongly detected.

As detailed so far, if a clock mark is defective due to a flaw, the present embodiment is capable of restoring the data division to byte-to-byte basis at the data segment where a next synchronization pattern exists. Thus, a highly reliable optical disk and optical disk device can be realized that are capable of preventing bit displacement caused by a defective clock mark from resulting in the data erroneously recorded in all subsequent data segments.

An optical disk in accordance with the present invention may be arranged so that the optical disk has a recording track constituted by sectors arranged in a concentric or spiral form, in which data is rewritable sector by sector, wherein

each of the sectors is divided into segments,

each of the segments includes a data field for recording data and a clock field having a different light reflectance from that of the data field, and

0050522-042000

the data field includes fields for recording a synchronization pattern.

The optical disk in accordance with the present invention may be arranged so that

each of the sectors includes at least one address segment where address information is located and data segments for recording data,

the address segment is located at a head of the sector,

a first data segment immediately subsequent to the address segment includes a field for recording a phase-introducing header pattern for use in data reproduction, and

the fields for recording the synchronization pattern are included at regular intervals in a second data segment immediately subsequent to the first data segment and data segments subsequent to the second data segment.

An optical reproduction device in accordance with the present invention may be an optical reproduction device for reproducing data from an optical disk with a recording track constituted by sectors arranged in a concentric or spiral form, in which data is rewritable sector by sector, wherein

each of the sectors is divided into segments, each of the segment includes data fields for recording data

00550522-042000

and a clock field having a different light reflectance from that of the data fields, and the data fields record synchronization patterns, and

the optical reproduction device may be arranged so that it includes:

clock generation means for detecting a laser reflected at the clock field as a clock field signal and generating a clock for use in data reproduction according to the clock field signal;

synchronization pattern detection means for detecting the synchronization pattern recorded in the data fields;

reproduction means for reproducing sector by sector using the clock generated by the clock generation means and correcting displacement of data in the sector according to a result of the detection of the synchronization pattern.

The optical reproduction device in accordance with the present invention may be arranged so that the synchronization pattern detection means includes window means for detecting the synchronization pattern only in a predetermined part in the data fields.

An optical recording device in accordance with the present invention may be an optical recording device for recording data on an optical disk with a recording track

00550522-012000

constituted by sectors arranged in a concentric or spiral form, in which data is rewritable sector by sector, wherein

each of the sectors is divided into segments, and each of the segment includes a data field for recording data and a clock field having a different light reflectance from that of the data field, and

the optical recording device may be arranged so that it includes:

clock generation means for detecting a laser reflected at the clock field as a clock field signal and generating a clock for use in data recording according to the clock field signal; and

recording means for recording synchronization patterns, together with recording data, in each data field at a predetermined cycle.

The optical disk in accordance with the present invention has synchronization patterns as well as clock marks; therefore, despite a missing clock mark, displacement of data can be corrected in each sector according to the synchronization pattern provided in the data field, enabling highly reliable recording and reproduction to be performed with few errors.

Further, if a further arrangement is made so that each of the sectors includes at least one address

00560522-042800

the address segment is located at the head of the sector,

the synchronization patterns are provided at regular intervals in a second data segment immediately subsequent to the first data segment and data segments subsequent to the second data segment, the clock and data can be adjusted in phase by using the header pattern in the first data segment after the address information located at the head of the sector is read. Further, since the synchronization patterns are provided at regular intervals, displacement of the data can be corrected after a certain period of time regardless of where the clock mark is missing. This advantage is enjoyed uniformly in any part of the disk.

The optical reproduction device in accordance with the present invention reproduces sector by sector using the clock generated from the clock mark and corrects the displacement of the data in the sector according to a result of the detection of the synchronization pattern; therefore, despite a displacement of data caused when

Further, if window means is used so that the synchronization pattern is detected only in a predetermined part in the data segment, the synchronization pattern becomes detectable with few errors and high reliability.

The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art intended to be included within the scope of the following claims.

WHAT IS CLAIMED IS:

1. An optical disk including data segments, for recording data, provided in each sector in a recording track, wherein

at least some of the data segments each include:

a clock mark field for recording a clock mark from which a clock signal is obtained; and

a synchronization field for recording a synchronization pattern with which displacement of the data is corrected.

2. The optical disk as set forth in claim 1, wherein the at least some of the data segments including a synchronization field are provided at regular intervals in each sector.

3. The optical disk as set forth in claim 1, wherein the synchronization field has a fixed position in each of the data segments.

4. The optical disk as set forth in claim 1, wherein one of the data segments, located at a head of each sector, records a header pattern for matching the clock signal and the data in phase.

0050522-042000

5. The optical disk as set forth in claim 1, wherein the data segments each include a pre-write field and a post-write field for offsetting displacement of the data that occurs when the data is recorded.

6. An optical disk with a recording track constituted by sectors arranged in a concentric or spiral form, in which data is rewritable sector by sector, wherein

each of the sectors is divided into segments,

each of the segments includes a data field for recording data and a clock field having a different light reflectance from that of the data field, and

the data field includes fields for recording a synchronization pattern.

7. The optical disk as defined in claim 6, wherein each of the sectors includes at least one address segment where address information is located and data segments for recording data,

the address segment is located at a head of the sector,

a first data segment immediately subsequent to the address segment includes a field for recording a phase-introducing header pattern for use in data reproduction,

00550222.042000

and

the fields for recording the synchronization pattern are included at regular intervals in a second data segment immediately subsequent to the first data segment and data segments subsequent to the second data segment.

8. An optical reproduction device for reproducing data recorded in data segments provided in each sector in a recording track of an optical disk,

said optical reproduction device comprising:

a clock generation circuit for generating a clock signal from a clock mark recorded in a clock mark field provided in the data segments; and

a data rearrangement circuit for detecting a synchronization pattern recorded in a synchronization field provided in at least some of the data segments to correct displacement of the data according to the detected synchronization pattern.

9. The optical reproduction device as set forth in claim 8, wherein

the data rearrangement circuit detects the synchronization pattern in each sector of the optical disk at regular intervals.

003470 33505560

the data rearrangement circuit includes a window circuit for detecting the synchronization pattern only in proximity to the synchronization field.

a phase adjusting circuit for matching the data and the clock signal in phase using a header pattern recorded in one of the data segments located at a head of each sector of the optical disk.

each of the sectors is divided into segments, each of the segment includes data fields for recording data and a clock field having a different light reflectance from that of the data fields, and the data fields record synchronization patterns,

said optical reproduction device comprising:

clock generation means for detecting a laser

adding a synchronization pattern for correcting displacement of the data to data recorded in at least some of the data segments.

15. The optical recording device as set forth in claim 14, wherein

the synchronization pattern addition circuit adds the synchronization pattern to the data recorded in the data segments provided at regular intervals in each sector of the optical disk.

16. The optical recording device as set forth in claim 14, wherein

the synchronization pattern addition circuit adds the synchronization pattern so that the synchronization pattern is recorded at a fixed position in each data segment.

17. An optical recording device for recording data on an optical disk with a recording track constituted by sectors arranged in a concentric or spiral form, in which data is rewritable sector by sector, wherein

each of the sectors is divided into segments, and each of the segment includes a data field for recording data and a clock field having a different light

00360522 042800

reflectance from that of the data field.

the optical recording device comprising:

clock generation means for detecting a laser reflected at the clock field as a clock field signal and generating a clock for use in data recording according to the clock field signal; and

recording means for recording synchronization patterns, together with recording data, in each data field using the clock at a predetermined cycle.

ABSTRACT OF THE DISCLOSURE

An optical disk has a recording track constituted by sectors arranged in a concentric or spiral form. Each sector is divided into segments, and each segment includes a data field where data is recorded and a clock mark field having a different light reflectance from that of the data field. The data field in the sector has synchronization patterns S. Hence, a highly reliable optical disk, optical reproduction device, and optical recording device can be offered that are capable of performing recording and reproduction even if a clock mark is defective due to a flaw.

09560522-042800

FIG. 1 (a)

AS 0	AS 1	DS 0	DS 1	...	DS 43	DS 44
---------	---------	---------	---------	-----	----------	----------

FIG. 1 (b)

CM field	Pre-Ambie field	Address field	Reserve
-------------	--------------------	------------------	---------

FIG. 1 (c)

CM field	Pre-Write field	Data field	Post-Write field
-------------	--------------------	---------------	---------------------

FIG. 2

SEGMENT NUMBER RECORDING DATA	DS0	DS1		DS2	DS3		...	DS43		DS44
		S	Data		S	Data		S	Data	
	Header			Data			...			

FIG. 3




FIG. 4




FIG. 5




FIG. 6 (a)

AS 0	DS 0	DS 1	...	DS 43	DS 44
---------	---------	---------	-----	----------	----------


FIG. 6 (b)

CM field	Pre-Amble field	Address field	Reserve
-------------	--------------------	------------------	---------

FIG. 6 (c)

CM field	Data field
-------------	---------------

FIG. 7






FIG. 9





FIG. 10



Attorney's Docket No.

Page 1 of 4

As a below named inventor, I hereby declare that: My residence, post office address and citizenship are as stated below next to my name. I believe I am the original, first and sole inventor (if only one name is listed at 201) below or an original, first and joint inventor (if plural names are listed at 201-208 below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

OPTICAL DISK, OPTICAL REPRODUCTION DEVICE, AND OPTICAL RECORDING DEVICE

which is described and claimed in:

- ☒ the specification attached hereto.
- ☐ the specification in U.S. Application Serial Number _____, filed on _____
- ☐ the specification in PCT international application Number _____,
filed on _____; and was amended on _____

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a). I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

[illegible]

I hereby claim the benefit under 35 U.S.C. §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below, and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of 35 U.S.C. §112, I acknowledge the duty to disclose material information as defined in 37 CFR §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

Prior U.S. Applications or PCT International Applications Designating the U.S-Benefit Under 35 U.S.C. §120					
U.S. Applications		Status (Check One)			
Application Serial No.	U.S. Filing Date	Patented	Pending	Abandoned	

PCT Applications Designating the U.S.					
Application No.	Filing Date	U.S. Serial No. Assigned			

CLAIM FOR BENEFIT OF PRIOR U.S. PROVISIONAL APPLICATION(S)
(35 U.S.C. § 119(e))

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below:

Applicant	Provisional Application Number	Filing Date

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) with full powers of association, substitution and revocation to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Sevalli P. Bronstein (Reg. No. 16,919)
David G. Conlin (Reg. No. 27,026)
George W. Neuner (Reg. No. 26,964)
Ernest V. Linek (Reg. No. 29,822)

Linda M. Buckley (Reg. No. 31,003)
Ronald I. Eisenstein (Reg. No. 30,628)
Henry D. Pahl, Jr. (Reg. No. 20,438)
Peter J. Manus (Reg. No. 26,766)

David S. Resnick (Reg. No. 34,235)
Peter F. Corless (Reg. No. 33,860)

SEND CORRESPONDENCE TO: Dike, Bronstein, Roberts & Cushman, LLP 130 Water Street Boston, Massachusetts 02109	DIRECT TELEPHONE CALLS TO: (617) 523-3400
--	---

2 0 1	FULL NAME OF INVENTOR RESIDENCE & CITIZENSHIP POST OFFICE ADDRESS	LAST NAME CITY POST OFFICE ADDRESS	FIRST NAME STATE OR FOREIGN COUNTRY CITY	MIDDLE NAME COUNTRY OF CITIZENSHIP STATE OR COUNTRY AND ZIP CODE
		Akiyama Kashihara-shi 2352-1, Mise-cho	Jun Nara Japan Kashihara-shi	 Japan Nara 634-0064 Japan

2 0 2	FULL NAME OF INVENTOR RESIDENCE & CITIZENSHIP POST OFFICE ADDRESS	LAST NAME CITY POST OFFICE ADDRESS	FIRST NAME STATE OR FOREIGN COUNTRY CITY	MIDDLE NAME COUNTRY OF CITIZENSHIP STATE OR COUNTRY AND ZIP CODE
		Maeda Yamatokoriyama-shi 2996-18, Koizumi-cho	Shigemi Nara Japan Yamatokoriyama-shi	 Japan Nara 639-1042 Japan

2 0 3	FULL NAME OF INVENTOR RESIDENCE & CITIZENSHIP POST OFFICE ADDRESS	LAST NAME CITY POST OFFICE ADDRESS	FIRST NAME STATE OR FOREIGN COUNTRY CITY	MIDDLE NAME COUNTRY OF CITIZENSHIP STATE OR COUNTRY AND ZIP CODE

2 0 4	FULL NAME OF INVENTOR RESIDENCE & CITIZENSHIP POST OFFICE ADDRESS	LAST NAME CITY POST OFFICE ADDRESS	FIRST NAME STATE OR FOREIGN COUNTRY CITY	MIDDLE NAME COUNTRY OF CITIZENSHIP STATE OR COUNTRY AND ZIP CODE

FULL NAME OF INVENTOR	LAST NAME	FIRST NAME	MIDDLE NAME
2 0 5 RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE OR COUNTRY AND ZIP CODE

FULL NAME OF INVENTOR	LAST NAME	FIRST NAME	MIDDLE NAME
1 0 6 RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE OR COUNTRY AND ZIP CODE

FULL NAME OF INVENTOR	LAST NAME	FIRST NAME	MIDDLE NAME
2 0 7 RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE OR COUNTRY AND ZIP CODE

FULL NAME OF INVENTOR	LAST NAME	FIRST NAME	MIDDLE NAME
2 0 8 RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE OR COUNTRY AND ZIP CODE

I hereby further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Signature of Inventor 201 <i>Jun Akiyama</i>	Signature of Inventor 202 <i>Shigami Maeda</i>
Date: April 4, 2000	Date: April 4, 2000